

Product Data

Outstanding Protection for Interior & Exterior Surfaces

Belzona® 5151 (Hi-Build Cladding) and Belzona® 5131 (EG-Cladding) are coatings for long term waterproofing and weatherproofing of exterior walls, interior walls, and structures.

Belzona® 5131 (EG-Cladding) has also built in energy conservation properties providing low thermal conductivity, which together with exceptionally low heat capacity, will make cold surfaces feel warm thus minimizing condensation, making warm surfaces feel cooler.

Belzona® 5131 (EG-Cladding) **Belzona® 5151 (Hi-Build Cladding) will:**

- Provide long term protection
- Extend building life
- Water and weatherproof structures
- Provide a seamless finish

Belzona® 5131 (EG-Cladding) and Belzona® 5151 (Hi-Build Cladding) can be applied without the need for specialist tools and are suitable for use on porous and non-porous substrates.

Belzona® 5131

EG-Cladding

Belzona® 5151

Hi-Build Cladding



Columns



Pipework



Internal Walls



Metal Roofs

Applications for **Belzona® 5131 (EG-Cladding)** **Belzona® 5151 (Hi -Build Cladding)** **include:**

- External walls
- Internal walls
- Ducting and pipework
- Ceilings
- Metal roofs and cladding
- Cold pipework
- Lintels
- Columns

www.belzona.com

Belzona provides the solution to your repair and maintenance needs.


BELZONA®
Repair • Protect • Improve

Belzona® 5131 (EG-Cladding) Belzona® 5151 (Hi -Build Cladding) are:

Simple

- Applied by brush or roller

Safe

- Cold temperature cure ensures no fire risk

Versatile

- Suitable for use on porous and non-porous substrates
- Can be applied to damp surfaces as micro-porosity allows substrate to dry out
- High flexible coating passing ASTM D522 1.5 inch conical mandrel and BS3900 : E1 0.5 inch cylindrical mandrel tests at temperatures as low as 14°F (-24°F) thus accommodating normal building movements

Effective

- Excellent waterproofing characteristics
- Reflection and refraction of radiation from sunlight reduces heat build up providing long term protection
- Low carbon dioxide permeability drastically reduces carbonation
- Outstanding stability in aggressive environments
- Offers self cleaning properties on external walls

For more information, please contact your local Belzona representative.



Belzona® 5131

EG-Cladding

Belzona® 5151

Hi-Build Cladding



External Walls

QUALITY PRODUCTS - TECHNICAL SUPPORT

The Belzona product range is manufactured through stringent quality and environmental control guidelines complying with the internationally recognized requirements of **ISO 9001:2008** and **ISO 14001:2004**. Belzona has a global distribution network of over 140 Distributors operating in 120 countries. Local support is provided by trained Technical Consultants who will diagnose the problem, recommend the solution, and provide 24-hour on-site application supervision.

Copyright© 2008 by Belzona International, Ltd. All rights reserved. No part of this work may be reproduced or used in any form or by any means - graphic, electronic, or mechanical including photocopying, recording, taping, or information storage and retrieval systems - without written permission of Belzona International, Ltd. Belzona® is a registered trademark.

www.belzona.com



ISO 9001:2008
Q 09335
ISO 14001:2004
EMS 509612

Europe & Africa
Belzona Polymers Ltd.
Harrogate, UK
t: +44 1423 567641
f: +44 1423 505967
e: belzona@belzona.co.uk

The Americas
Belzona Inc.
Miami, FL USA
t: +1 (305) 594-4994
f: +1 (305) 599-1140
e: belzona@belzona.com

Asia & Oceania
Belzona Asia Pacific
Chonburi, Thailand
t: +66 38 491031
f: +66 38 491102
e: belzona@belzona.cn

China
Belzona Hong Kong
Hong Kong, China
t: +852 3101 7461
f: +852 3101 7530
e: belzona@belzona.hk


BELZONA®
Repair • Protect • Improve