Safety Data Sheet

Product: **BELZONA® 1591**
Date: **OCTOBER 1998**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION	Belzona Polymerics Ltd. Claro Road, Harrogate, HG1 4AY. Tel: +44 (0) 1423 567641 Emergency Tel: +44 (0) 1423 503218	Product Type: Two-pack material for repair and reclamation of machinery and equipment
	BASE	**SOLIDIFIER**
2. COMPOSITION/INFORMATION ON INGREDIENTS	Epoxy phenol novolac resin 10-30%	Diethylenetriamine 10-30% Cycloaliphatic amine preparation 60-100%
3. HAZARDS IDENTIFICATION	Irritating to eyes and skin (R36/38). May cause sensitization by skin contact (R43).	Harmful if swallowed (R22). Causes severe burns (R35). May cause sensitization by skin contact (R43).
4. FIRST AID MEASURES		
Inhalation	Remove to fresh air.	Remove to fresh air.
Skin	Remove excess with clean cloth and wash skin thoroughly with soap and water. If irritation persists seek medical attention.	Flush immediately with copious amounts of water for at least 15 minutes. In the event of any irritation or inflammation seek medical attention immediately.
Eyes	Rinse immediately with copious amounts of water for at least 15 minutes. If irritation persists seek medical attention.	Flush immediately with copious amounts of water for at least 15 minutes and seek immediate medical attention.
Ingestion	Do not induce vomiting. Immediately rinse mouth with water. Drink plenty of water. Seek medical attention promptly.	Do not induce vomiting. Immediately rinse mouth with water. Drink 1/3 pint water every 10 minutes for 30 minutes. Seek medical attention promptly.
5. FIRE-FIGHTING MEASURES		
Extinguishing Media	Dry powder, foam or carbon dioxide.	Dry powder, foam or carbon dioxide.
Unsuitable	Water jet.	Water jet
Special Procedures	Fire fighters must wear self contained breathing apparatus due to the toxic nature of evolved gases.	Fire fighters must wear self contained breathing apparatus due to the toxic nature of evolved gases.
6. ACCIDENTAL RELEASE MEASURES		
Personal Precautions	Wear suitable protective clothing, gloves and eye/face protection (S36/37/39)	Wear suitable protective clothing, gloves and eye/face protection (S36/37/39)
Environmental Precautions	Do not empty into drains (S29). Do not allow to contaminate water, effluent or soil. Observe Local Bye Laws.	Do not empty into drains (S29). Do not allow to contaminate water, effluent or soil. Observe Local Bye Laws.
Cleansing Methods	Absorb with dry inert material such as sand. Place into suitable labelled containers for disposal.	Absorb with dry inert material such as sand. Place into suitable labelled containers for disposal. Flush contaminated area with detergent and water.
7. HANDLING AND STORAGE	Avoid contact with skin and eyes (S24/25). Do not breathe vapour/spray (S23) Use only in well ventilated areas (S51). When using do not eat, drink or smoke (S20/21). Store in tightly lidded containers in dry conditions between 5ºC and 30ºC.	Avoid breathing vapour Avoid contact with skin and eyes (S24/25). Use only in well ventilated areas (S51). When using do not eat, drink or smoke (S20/21). Store in tightly lidded containers in dry conditions between 5˚C and 30˚C.
8. EXPOSURE CONTROLS AND PERSONAL PROTECTION		
Respiratory	In confined areas or where good natural/mechanical ventilation is not available respiratory protection should be used.	In confined areas or where good natural/mechanical ventilation is not available leading to a risk of exceeding the exposure limits indicated, respiratory protection should be used.
Hands	Impermeable nitrile or neoprene gloves.	Impermeable nitrile or neoprene gloves.
Eyes	Faceshield/Goggles	Faceshield/Goggles
Other	Suitable protective clothing.	Suitable protective clothing

	BASE	SOLIDIFIER
9. PHYSICAL AND CHEMICAL PROPERTIES		
Boiling point	> 250°C	> 100°C
Flash Point (Closed Cup)	> 110°C	> 90°C
Flammability	Non-flammable, but combustible.	Non-flammable, but combustible.
Autoflammability	No information available	No information available
Explosive Properties	Not applicable	Not applicable
Oxidising Properties	Not applicable	Not applicable
Vapour Pressure	Not applicable	No information available
Relative Density	1.90	1.01
Solubility in Water	Insoluble	Insoluble
Other Data	Exothermic reactions occur when components are mixed. Avoid storage of mixed material in sealed containers.	Exothermic reactions occur when components are mixed. Avoid storage of mixed material in sealed containers.
10. STABILITY AND REACTIVITY	Stable	Stable
Conditions to Avoid	Not applicable	Not applicable
Materials to Avoid	Strong oxidising agents, acids and bases. Amines under uncontrolled conditions.	Strong oxidising agents, acids and isocyanates. Epoxy resins under uncontrolled conditions.
Hazardous Decomposition Products	Gaseous combinations of carbon, hydrogen and oxygen.	Gaseous combinations of carbon, hydrogen, oxygen and nitrogen.
11. TOXICOLOGICAL INFORMATION	Epoxy phenol novolac resin: Oral LD_{50} (rat) > 5000 mg kg^{-1}	Diethylenetriamine: OES (8hr TWA) 1 ppm, 4 mg m^{-3} Oral LD_{50} (rat) 1080 mg kg^{-1} Dermal LD_{50} (rabbit) 1090 mg kg^{-1}
12. ECOLOGICAL INFORMATION	Epoxy phenol novolac resin: Not readily biodegradable Toxicity to daphnia: EC_{50} Daphnia magna Straus 1820 Dose - 3.5 mgL^{-1}, Period 48h, method OECD 202 Toxicity to fish: LC_{50} Golden orfe Dose - 5.7 mgL^{-1}, Period 96h, method OECD 203	Waste from this product may present long term environmental hazards, thus landfill disposal must be condisered less acceptable than incineration.
13. DISPOSAL	Excess product should be mixed and allowed to solidify before disposal. Disposal must be carried out in accordance with Local and National Regulations.	Excess product should be mixed and allowed to solidify before disposal. Disposal must be carried out in accordance with Local and National Regulations.
14. TRANSPORT INFORMATION		
Hazard Warning	Not applicable	Corrosive
UN No.	Not applicable	1760
IMO/IMDG	Not applicable	Class 8/8147
ICAO/IATA	Not applicable	Class 8 1760 III
RID/ADR	Not applicable	Class 8 No 66° (c)
15. REGULATORY INFORMATION		
Hazard	Irritant	Corrosive
Risk Phrases	Irritating to eyes and skin (R36/38). May cause sensitization by skin contact (R43).	Harmful if swallowed (R22). Causes severe burns (R35). May cause sensitization by skin contact (R43).
Safety Phrases	Avoid contact with skin and eyes (S24/25). In case of contact with eyes rinse immediately with plenty of water and seek medical advice (S26). After contact with skin, wash immediately with plenty of soap and water (S28). Wear suitable gloves and eye/face protection. Contains epoxy constituents. See information supplied by manufacturer.	Avoid contact with skin and eyes (S24/25). In case of contact with eyes rinse immediately with plenty of water and seek medical advice (S26). Wear suitable protective clothing. Wear suitable gloves and eye/face protection (S28). In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).
16. OTHER INFORMATION	Adequate ventilation is that which ensures that the oxygen content of the air being breathed is greater than 18% and that any airborne contaminants with occupational exposure limits do not exceed quoted MEL or OES values.	Adequate ventilation is that which ensures that the oxygen content of the air being breathed is greater than 18% and that any airborne contaminants with occupational exposure limits do not exceed quoted MEL or OES values.

Copyright © 1998 by Belzona International Limited. All rights reserved. No part of this work covered by the copyrights hereon may be reproduced or used in any form or by any means - graphic, electronic or mechanical including photocopying, recording, taping or information storage and retrieval systems - without written permission of the publisher.

Belzona® is a registered trademark

Printed in England Publication No. 4-10-98

Belzona Polymerics Ltd.,
Claro Road,
Harrogate, HG1 4AY,
England.
Tel: +44 (0) 1423 567641
Fax: +44 (0) 1423 505967

Belzona Inc.,
2000 N.W. 88 Court,
Miami, Florida 33172,
U.S.A.
Tel: +1 (305) 594 4994
Fax: +1 (305) 599 1140

BS EN ISO 9002 : 1994
Certificate No Q/09335