MATERIAL SAFETY DATA SHEET
In compliance with OSHA 29 CFR 1910.1200
N.ap means Not Applicable NIA means No Information Available

PREPARED BY : N.A.ROBINSON DATE PREPARED : 28 MAR 2000

BELZONA INC., 2000 N.W. 88 COURT, MIAMI, FL 33172	EMERGENCY PHONE NUMBERS (Spill, Leak, Fire, Exposure or Accident) 800 424 9300 - Toll free in United States 202 483 7616 - For calls from outside the United States INFORMATION PHONE NUMBER 305 594 4994 - Working hours only

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER : 1004/1471
PRODUCT NAME : Belzona® 1521 Base
PRODUCT CLASS : Modified epoxide resin

SECTION II - HAZARDOUS INGREDIENTS/TOXICOLOGICAL DATA

Hazardous Components	% by Weight	CAS Number	Exposure Limits OSHA PEL mg/m^3	ACGIH TLV ppm	ACGIH TLV mg/m^3	Toxicity LD_{50} Oral mg/Kg	LD_{50} Dermal mg/Kg	LC_{50} Inhal ppm
Epoxy phenol novolac resin	10-30	28064-14-4	NIA	NIA	NIA	5000	6000	NIA
Butanedioldiglycidyl ether	1-5	2425-79-8	NIA	NIA	NIA	2000	NIA	NIA
Silicon carbide	10-30	409-21-2	NIA	N.ap	10	NIA	NIA	NIA

CARCINOGENICITY
No data is available for the mixture, however, none of the ingredients are listed as carcinogens by OSHA, NTP, ACGIH or IARC.

SECTION III - PHYSICAL DATA

APPEARANCE AND ODOR : Dark brown liquid with no discernible odor.
BOILING POINT : >250°C
VAPOR PRESSURE : NIA
EVAPORATION RATE : N.ap
SOLUBILITY IN WATER : None
SPECIFIC GRAVITY : 1.80
VAPOR DENSITY : NIA
% VOLATILE BY VOLUME : N.ap

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : >100°C
TEST METHOD : Closed cup
EXPLOSION LIMITS LOWER : NIA
UPPER : NIA

OSHA FLAMMABILITY CLASS : N.ap
FLAMMABILITY INDEX (NFPA) : 1 Slight
REACTIVITY INDEX (NFPA) : 1 Slight
HEALTH HAZARD (NFPA) : 2 Moderate
EXTINGUISHING MEDIA : Water fog (not a direct stream of water), foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES
Wear protective clothing and use self-contained breathing apparatus. Full bunker gear should be worn in extreme cases. Use sand to contain burning material.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Decomposition and combustion products may be hazardous.

SECTION V - HEALTH HAZARDS

ROUTE(S) OF ENTRY : Skin contact, skin absorption, eye contact.
PRIME HAZARD(S) : Skin sensitizer and skin irritation.

EFFECTS OF EXPOSURE
Acute : Skin and eye irritation
Chronic : Irritation, sensitization and dermatitis

EMERGENCY AND FIRST AID PROCEDURES
Inhalation : If symptoms are experienced, remove source of contamination and/or move victim to fresh air. If recovery is delayed or there are signs of distress obtain medical attention immediately.

Eye contact : Flush eyes with water for 15 minutes. Seek medical advice if any irritation persists.

Skin contact : Immediately remove excess with a clean cloth and wash skin thoroughly with soap and water. If irritation or inflammation persists, seek medical advice.

Ingestion : If swallowed, do not induce vomiting. Rinse mouth with water and drink plenty of water. Call TAMPA BAY Regional Poison Center (Tel.No.1-800-282-3171) and/or seek medical advice.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
Skin and eye conditions.

SECTION VI - REACTIVITY DATA

STABILITY : Stable
STABILITY CONDITIONS TO AVOID : N.ap

INCOMPATIBILITY (MATERIALS TO AVOID CONTACT WITH)
Strong oxidizing agents, acids, bases and amines.

HAZARDOUS DECOMPOSITION PRODUCTS
Gaseous combinations of carbon, hydrogen and oxygen may occur.

HAZARDOUS POLYMERIZATION
Hazardous polymerization will not occur when stored and used as directed.

POLYMERIZATION CONDITIONS TO AVOID
N.ap

SECTION VII - SPILL AND LEAK PROCEDURES

SPILLAGE
Absorb with an inert material (e.g. earth or sand). Sweep up, place into suitable labelled containers, seal and dispose of properly. Flush area with detergent and water.

WASTE DISPOSAL METHODS
Dispose of in accordance with Local, State and Federal Regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

PERSONAL PROTECTIVE MEASURES

RESPIRATORY : In confined areas or where good natural/mechanical ventilation is not available an appropriate NIOSH or MSHA approved respirator should be worn.

SKIN : Impermeable gloves, such as Neoprene or Nitrile. Wash hands with soap and water and use hand cream. Suitable protective clothing to minimize skin contact. Remove contaminated clothing and wash before reuse.

EYE : Safety glasses or goggles. Eyewash station.

MECHANICAL PROTECTIVE MEASURES

VENTILATION : Where adequate natural ventilation is not available provide suitable local exhaust ventilation.

OTHER PROTECTIVE EQUIPMENT

: Where there is a risk of contamination of footwear, safety boots should be worn and cleaned thoroughly before reuse.

OTHER COMMENTS

: Where machining or abrading of cured material leads to the production of respirable and/or nuisance dust, an appropriate NIOSH or MSHA approved respirator should be worn.

SECTION IX - SAFE HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS

HANDLING

Avoid breathing vapours and contact with skin and eyes.

STORAGE

Overheating may cause containers to rupture. Containers should be stored under cool, dry conditions. Empty containers will retain residue and may be dangerous. Check all containers for leaks at regular intervals and before use.

HYGIENE PRACTICES

When using, do not eat, drink or smoke. Remove contaminated clothing and launder before reuse. Wash hands with soap and water after handling this product.

SECTION X - REGULATORY INFORMATION

SARA TITLE III - NOTIFICATION OF TOXIC CHEMICALS

None of the constituents of this product are subject to reporting requirements under section 313 of the Superfund Amendment and Reauthorization Act of 1986 (40 CFR Part 372).

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, some of the information presented and conclusions drawn are derived from sources other than direct test data on the product itself and while Belzona Inc. believe such sources to be reliable, the information is provided without any warranty regarding its correctness.
Since Belzona Inc. has no control over the conditions under which the product will be used, liability will not be assumed to exceed replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties including implied warranties of merchantability or fitness for a particular purpose. Belzona Inc. assumes no liability for injury or incidental or consequential damage arising out of the storage, handling, use or disposal of this product.

MATERIAL SAFETY DATA SHEET
In compliance with OSHA 29 CFR 1910.1200
N.ap means Not Applicable NIA means No Information Available

PREPARED BY : N.A.ROBINSON DATE PREPARED : 28 MAR 2000

BELZONA INC., 2000 N.W. 88 COURT, MIAMI, FL 33172	EMERGENCY PHONE NUMBERS (Spill, Leak, Fire, Exposure or Accident) 800 424 9300 - Toll free in United States 202 483 7616 - For calls from outside the United States INFORMATION PHONE NUMBER 305 594 4994 - Working hours only

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NUMBER : 1101/1472
PRODUCT NAME : Belzona® 1521 Solidifier
PRODUCT CLASS : Modified polyamine

SECTION II - HAZARDOUS INGREDIENTS/TOXICOLOGICAL DATA

Hazardous Components	% by Weight	CAS Number	Exposure Limits OSHA PEL mg/m^3	ACGIH TLV ppm	ACGIH TLV mg/m^3	Toxicity LD_{50} Oral mg/Kg	LD_{50} Dermal mg/Kg	LC_{50} Inhal ppm
Diethylenetriamine	5-10	111-40-0	NIA	1	4	1080	1090	NIA
Cycloaliphatic amine preparation (Trade Secret)	10-30	05995500-5409P/5422P	NIA	NIA	NIA	NIA	NIA	NIA
4'4'-methylenebis (cyclohexanamine)	30-60	1761-71-3	NIA	NIA	NIA	>625	>2110	>10mg/L/1hr
Bisphenol A	1-5	80-05-7	NIA	NIA	NIA	2000	3000	NIA

CARCINOGENICITY
No data is available for the mixture, however, none of the ingredients are listed as carcinogens by OSHA, NTP, ACGIH or IARC.

SECTION III - PHYSICAL DATA

APPEARANCE AND ODOR : Grey liquid with amine odor.
BOILING POINT : >100°C
VAPOR PRESSURE : NIA
EVAPORATION RATE : NIA
SOLUBILITY IN WATER : Moderate
SPECIFIC GRAVITY : 1.67
VAPOR DENSITY : NIA
% VOLATILE BY VOLUME : N.ap

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT : >100°C
TEST METHOD : Setaflash
EXPLOSION LIMITS LOWER : NIA
UPPER : NIA

OSHA FLAMMABILITY CLASS : Combustible liquid - CLASS IIIB
FLAMMABILITY INDEX (NFPA) : 1 Slight
REACTIVITY INDEX (NFPA) : 1 Slight
HEALTH HAZARD (NFPA) : 3 Serious
EXTINGUISHING MEDIA : Water fog (not a direct stream of water), foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES
Wear protective clothing and use self-contained breathing apparatus. Full bunker gear should be worn in extreme cases. Use sand to contain burning material.

UNUSUAL FIRE AND EXPLOSION HAZARDS
Decomposition and combustion products may be hazardous.

SECTION V - HEALTH HAZARDS

ROUTE(S) OF ENTRY : Skin contact, skin absorption, eye contact, inhalation.
PRIME HAZARD(S) : Corrosive.

EFFECTS OF EXPOSURE
Acute : Causes burns to skin and eyes. Respiratory tract irritant.
Chronic : Chemical burns and sensitization.

EMERGENCY AND FIRST AID PROCEDURES
Inhalation : If symptoms are experienced, remove source of contamination and/or move victim to fresh air. If recovery is delayed or there are signs of distress obtain medical attention immediately.

Eye contact : Flush eyes with water for 15 minutes. Immediate first aid is necessary to prevent eye damage. Seek medical advice if any irritation persists.

Skin contact : Immediately remove excess with a clean cloth and wash skin thoroughly with soap and water. If irritation or inflammation persists, seek medical advice.

Ingestion : If swallowed, do not induce vomiting. Rinse mouth with water and drink 1 cup of water every 10 minutes for 30 minutes. Call TAMPA BAY Regional Poison Center (Tel.No.1-800-282-3171) and/or seek medical advice.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
Skin, eye and respiratory conditions.

SECTION VI - REACTIVITY DATA

STABILITY : Stable
STABILITY CONDITIONS TO AVOID : N.ap

INCOMPATIBILITY (MATERIALS TO AVOID CONTACT WITH)
Strong oxidizing agents, acids, epoxy resins and isocyanates.

HAZARDOUS DECOMPOSITION PRODUCTS
Gaseous combinations of carbon, hydrogen, nitrogen and oxygen may occur at elevated temperatures.

HAZARDOUS POLYMERIZATION
Hazardous polymerization will not occur when stored and used as directed.

POLYMERIZATION CONDITIONS TO AVOID
N.ap

SECTION VII - SPILL AND LEAK PROCEDURES

SPILLAGE
Absorb with an inert material (e.g. earth or sand). Sweep up, place into suitable labelled containers, seal and dispose of properly. Flush area with detergent and water.

WASTE DISPOSAL METHODS
Dispose of in accordance with Local, State and Federal Regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

PERSONAL PROTECTIVE MEASURES

RESPIRATORY : In confined areas or where good natural/mechanical ventilation is not available, leading to a risk of exceeding the TLV's indicated, an appropriate NIOSH or MSHA approved respirator should be worn.

SKIN : Impermeable gloves, such as Neoprene or Nitrile. Wash hands with soap and water and use hand cream. Suitable protective clothing to minimize skin contact. Remove contaminated clothing and wash before reuse.

EYE : Safety glasses or goggles. Eyewash station.

MECHANICAL PROTECTIVE MEASURES

VENTILATION : Where adequate natural ventilation is not available provide suitable local exhaust ventilation.

OTHER PROTECTIVE EQUIPMENT

: Where there is a risk of contamination of footwear, safety boots should be worn and cleaned thoroughly before reuse.

OTHER COMMENTS

: Where machining or abrading of cured material leads to the production of respirable and/or nuisance dust, an appropriate NIOSH or MSHA approved respirator should be worn.

SECTION IX - SAFE HANDLING AND STORAGE

HANDLING AND STORAGE PRECAUTIONS

HANDLING

Avoid breathing vapors and contact with skin and eyes.

STORAGE

Overheating may cause containers to rupture. Containers should be stored under cool, dry conditions. Empty containers will retain residue and may be dangerous. Check all containers for leaks at regular intervals and before use.

HYGIENE PRACTICES

When using, do not eat, drink or smoke. Remove contaminated clothing and launder before reuse. Wash hands with soap and water after handling this product.

SECTION X - REGULATORY INFORMATION

SARA TITLE III - NOTIFICATION OF TOXIC CHEMICALS

Bisphenol A, CAS Number 80-05-7, a constituent of this product at 1-5% by weight, is subject to reporting requirements under section 313 of the Superfund Amendment and Reauthorization Act of 1986 (40 CFR Part 372).

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, some of the information presented and conclusions drawn are derived from sources other than direct test data on the product itself and while Belzona Inc. believe such sources to be reliable, the information is provided without any warranty regarding its correctness.
Since Belzona Inc. has no control over the conditions under which the product will be used, liability will not be assumed to exceed replacement or refund of the purchase price of this product. Except as stated herein, there are no express or implied warranties including implied warranties of merchantability or fitness for a particular purpose. Belzona Inc. assumes no liability for injury or incidental or consequential damage arising out of the storage, handling, use or disposal of this product.