WHMIS MATERIAL SAFETY DATA SHEET

SECTION 1 - Product Identification and Use			Date : **13 October, 2000**
Product identifier : **BELZONA® 2211 (MP HI-BUILD ELASTOMER) BASE**			PIN/UN No : **Not applicable**
Product use : **Repair and Reclamation**			WHMIS classification : **D1A**
Manufacturer's name & address : **BELZONA POLYMERICS Ltd.,** Claro Road, Harrogate, Yorkshire, HG1 4AY, United Kingdom. Emergency telephone number : U.K. -44-1423-503218	Supplier's name & address : **BELZONA Inc.,** 2000 N.W. 88 Court, America's Gateway Park, Miami, Florida 33172, United States.	Supplier's emergency telephone numbers : (Spill, Leak, Fire, Exposure or Accident) 800 424 9300 - Toll free in Canada 202 483 7616 Information telephone number : 305 594 4994 - Working hours only	

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Approximate Concentration	CAS Numbers	Exposure Limits	LD_{50}/LC_{50} Species and Route
Toluene diisocyanate (TDI)	**0.1-1%**	**584-84-9**	**ACGIH (TWA) TLV = 0.005 ppm**	**Oral LD_{50} = 5800 mg/kg rat** **IHL LC_{50} = 14 ppm/4H rat**
Di-sec-octyl phthalate	**1-5%**	**117-81-7**	**ACGIH (TWA) TLV = 5 mg/m³**	**Oral LD_{50} = 3000 mg/kg rat**

SECTION 3 - Physical Data

Physical state : **Paste**	Appearance/Odour : **Black/odourless or no characteristic odour**	Odour threshold(ppm) : **Not applicable**
Vapour pressure (mm Hg) : **Not available**	Vapour density (Air = 1) : **>1**	Boiling point (°C) : **>150**
pH : **Not applicable**	Specific gravity : **1.09**	Coefficient water/oil : **Not applicable**
Freezing point (°C) : **Not applicable**	Solubility in water (20°C) : **Reacts**	Evaporation rate (relative to n-Butyl Acetate) : **Not applicable**

SECTION 4 - Fire and Explosion Data

Flammability : If yes, under which conditions :	**Not flammable but combustible.**	
Means of extinction :	**Dry powder, carbon dioxide, chemical foam or water fog.**	
Special procedures :	**Wear protective clothing and use self-contained breathing apparatus. Full bunker gear should be worn in extreme cases. Use sand to contain burning material.**	
Flash point and method : **> 100°C Closed cup**	Explosion limits (% by volume) : Lower : **Not applicable** Upper : **Not applicable**	Autoignition temp (°C) : **Not available**
Hazardous combustion products : **Gaseous combinations of carbon, hydrogen, nitrogen and oxygen**		
Explosion data - Sensitivity to impact : **Not applicable**	Explosion data - Sensitivity to static discharge : **Not applicable**	

SECTION 5 - Reactivity Data

Chemical stability : If no, under which conditions :	**Yes**
Incompatibility to other substances : If yes, which ones :	**Yes** **Water, alcohols, strong oxidizing agents, amines**
Reactivity and under what conditions :	**Reacts with water/moisture to generate carbon dioxide**
Hazardous decomposition products :	**See hazardous combustion products above**

Product identifier : **BELZONA® 2211 (MP HI-BUILD ELASTOMER) BASE**

SECTION 6 - Toxicological Properties of Product

Route of entry :
Skin contact : √ Skin absorption : Eye contact : √ Inhalation acute : √ Inhalation chronic : √ Ingestion : √

Effects of acute exposure to product : **Very toxic by inhalation.**

Effects of chronic exposure to product : **Possible risk of irreversible effects †.**

LD_{50} of product (species and route) : **Not available**	Irritancy of product : **Irritating to eyes, skin and respiratory system.**	Exposure limits of product : **See TLV for TDI**
LC_{50} of product (species and route) : **Not available**	Sensitization to product : **Respiratory and skin (TDI)**	Synergistic materials : **Not available**

Carcinogenicity : † Reproductive effects : † Teratogenicity : **N.av*** Mutagenicity : **N.av***

† Toluene diisocyanate is listed by IARC as a Group 2B carcinogen (Possibly carcinogenic to humans), and is listed by ACGIH as 'A3' (confirmed animal carcinogen with unknown relevance to humans). Within the EC Di-sec-octyl phthalate is classified as a Category 3 reprotoxin - substances which cause concern for human fertility, on the basis of results in appropriate animal studies.
*** Not available for the mixture.**

SECTION 7 - Preventative Measures

Personal protective equipment :	Gloves : **Neoprene or nitrile**	Eye : **Goggles/faceshield**
Footwear : **Safety shoes**	Respiratory (protection required if exposure > TLV) : **Face mask with isocyanate canister**	Clothing : **Overalls**

Other :

Engineering controls :	**Where adequate natural ventilation is not available provide suitable local exhaust ventilation.**
Leak and spill procedures :	**Absorb with a dry inert material (e.g. sand). Sweep up and place into suitable labelled containers. Dispose of properly. Flush area with dilute ammonium hydroxide or water/alcohol.**
Waste disposal :	**In accordance with Federal, Provincial and Local Regulations.**
Handling procedures :	**Avoid breathing vapors and contact with skin and eyes.**
Storage requirements :	**Keep in a cool well ventilated place in the original containers.**

SECTION 8 - First Aid Measures

Skin :	**After contact with skin wash immediately with plenty of soap and water.**
Eye :	**In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if any irritation persists.**
Inhalation :	**If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical attention immediately if recovery is delayed.**
Ingestion :	**Do not induce vomiting. Immediately rinse the mouth with water. Drink plenty of water (1 pint/600 mls.). Seek medical attention promptly.**
General advice :	**When using do not eat, drink or smoke. Take off immediately all contaminated clothing and launder before reuse. Wash hands thoroughly after handling this product.**

SECTION 9 - Preparation Date of MSDS

Additional information : **Replaces previous issue dated 7 October 1997**

Prepared by :	Phone number :	Date :
N.A.Robinson	**U.K. -44-1423-567641**	**13 October, 2000**

WHMIS MATERIAL SAFETY DATA SHEET

SECTION 1 - Product Identification and Use		Date : **13 October, 2000**
Product identifier : **BELZONA® 2211 (MP HI-BUILD ELASTOMER) SOLIDIFIER**		PIN/UN No : **Not applicable**
Product use : **Repair and Reclamation**		WHMIS classification: **D2B**
Manufacturer's name & address : **BELZONA POLYMERICS Ltd.,** Claro Road, Harrogate, Yorkshire, HG1 4AY, United Kingdom. Emergency telephone number : U.K. -44-1423-503218	Supplier's name & address : **BELZONA Inc.,** 2000 N.W. 88 Court, America's Gateway Park, Miami, Florida 33172, United States.	Supplier's emergency telephone numbers : (Spill, Leak, Fire, Exposure or Accident) 800 424 9300 - Toll free in Canada 202 483 7616 Information telephone number : 305 594 4994 - Working hours only

SECTION 2 - Hazardous Ingredients

Hazardous Ingredients	Approximate Concentration	CAS Numbers	Exposure Limits	LD_{50}/LC_{50} Species and Route
Phenylmercuric neodecanoate	**0.1-1%**	**26545-49-3**	**ACGIH (TWA) TLV 0.01 mg/m³**	**Oral LD_{50} 60mg/kg rat**
Polyether polyol	**5-10%**	**25322-69-4**	**Not available**	**Oral LD_{50} 1000-2000 mg/kg rat**
Diethylmethylbenzenediamine	**5-10%**	**68479-98-1**	**10 ppb (sk) MAK value (TWA)**	**Oral LD_{50} 472 mg/kg rat Dermal LD_{50} 1000 mg/kg rat**

SECTION 3 - Physical Data

Physical state : **Paste**	Appearance/Odour : **Off-white/odourless or no characteristic odour**	Odour threshold(ppm) : **Not applicable**
Vapour pressure (mm Hg) : **Not available**	Vapour density (Air = 1) : **>1**	Boiling point (°C) : **>100**
pH : **Not applicable**	Specific gravity : **1.49**	Coefficient water/oil : **Not available**
Freezing point (°C) : **Not available**	Solubility in water (20°C) : **Partially miscible**	Evaporation rate (relative to n-Butyl Acetate) : **Not applicable**

SECTION 4 - Fire and Explosion Data

Flammability : If yes, under which conditions :	**Not flammable but combustible.**	
Means of extinction :	**Water fog, foam, carbon dioxide or dry powder**	
Special procedures :	**Wear protective clothing and use self-contained breathing apparatus. Full bunker gear should be worn in extreme cases. Use sand to contain burning material.**	
Flash point and method : **> 100°C Closed Cup**	Explosion limits (% by volume) : Lower : **Not applicable** Upper : **Not applicable**	Autoignition temp (°C) : **Not available**
Hazardous combustion products : **Gaseous combinations of carbon, hydrogen, nitrogen, oxygen and mercury**		
Explosion data - Sensitivity to impact : **Not applicable**	Explosion data - Sensitivity to static discharge : **Not applicable**	

SECTION 5 - Reactivity Data

Chemical stability : If no, under which conditions :	**Yes**
Incompatibility to other substances : If yes, which ones :	**Yes** **Strong oxidising agents and isocyanates**
Reactivity and under what conditions :	**Not applicable**
Hazardous decomposition products :	**See hazardous combustion products above**

Product identifier : **BELZONA® 2211 (MP HI-BUILD ELASTOMER) SOLIDIFIER**

SECTION 6 - Toxicological Properties of Product

Route of entry :
Skin contact : √ Skin absorption : √ Eye contact : √ Inhalation acute : √ Inhalation chronic : Ingestion : √

Effects of acute exposure to product :	**Harmful by inhalation, in contact with skin and if swallowed.**
Effects of chronic exposure to product :	**Harmful: danger of serious damage to health through prolonged exposure if swallowed.**

LD_{50} of product (species and route) : **Not available**	Irritancy of product : **Irritating to eyes and skin**	Exposure limits of product : **See Section 2**
LC_{50} of product (species and route) : **Not available**	Sensitization to product : **Not applicable**	Synergistic materials : **Not available**

Carcinogenicity : √ Reproductive effects : **N.av*** Teratogenicity : **N.av*** Mutagenicity : **N.av***

*** Not available for product, however, our supplier indicates that diethylmethylbenzenediamine has been shown to be carcinogenic in laboratory animals. Diethylmethylbenzenediamine is not listed within the IARC monographs or ACGIH.**

SECTION 7 - Preventative Measures

Personal protective equipment :	Gloves : **Neoprene or nitrile**	Eye : **Goggles/faceshield**
Footwear : **Industrial boots**	Respiratory (protection required if exposure > TLV) : **Face mask with organic vapour canister**	Clothing : **Overalls**

Other :

Engineering controls :	**Where adequate natural ventilation is not available provide suitable local exhaust ventilation.**
Leak and spill procedures :	**Contain with an inert material (e.g. earth or sand). Sweep up and place into suitable covered, labelled containers. Flush area with detergent and water.**
Waste disposal :	**In accordance with Federal, Provincial and Local Regulations.**
Handling procedures :	**Avoid contact with skin and eyes. Do not breathe fumes/vapour.**
Storage requirements :	**Keep in a cool, well ventilated place, in the original containers.**

SECTION 8 - First Aid Measures

Skin :	**After contact with skin, wash immediately with plenty of soap and water.**
Eye :	**In case of contact with eyes, rinse immediately with plenty of water and seek medical advice if any irritation persists.**
Inhalation :	**If symptoms are experienced, remove source of contamination or move victim to fresh air. Obtain medical attention immediately if recovery is delayed.**
Ingestion :	**Do not induce vomiting. Immediately rinse the mouth with water. Drink plenty of milk. Seek medical attention promptly.**
General advice :	**When using do not eat, drink or smoke. Take off immediately all contaminated clothing and launder before reuse. Wash hands thoroughly after handling this product.**

SECTION 9 - Preparation Date of MSDS

Additional information : **Replaces previous issue dated 7 October 1997**

Prepared by :	Phone number :	Date :
N.A.Robinson	**U.K. -44-1423-567641**	**13 October, 2000**